

# MODEL EHJ

## HORSEPOWER SELECTION GUIDE (no height limitation)

Motor	Door of wood or aluminum	Fiberglass	Steel door 20 ga.	Rolling steel	Unbalanced door wt.
1/3 H.P. 249W	320 sq. ft. 30m <sup>2</sup>	576 sq. ft. 54m <sup>2</sup>	288 sq. ft. 27m <sup>2</sup>	288 sq. ft. 27m <sup>2</sup>	1200 lbs. 544kg
1/2 H.P. 373W	400 sq. ft. 37m <sup>2</sup>	624 sq. ft. 58m <sup>2</sup>	320 sq. ft. 30m <sup>2</sup>	320 sq. ft. 30m <sup>2</sup>	1500 lbs. 680kg
3/4 H.P. 560W	576 sq. ft. 54m <sup>2</sup>	672 sq. ft. 62m <sup>2</sup>	400 sq. ft. 37m <sup>2</sup>	400 sq. ft. 37m <sup>2</sup>	2000 lbs. 907kg
1 H.P. 746W	624 sq. ft. 58m <sup>2</sup>	720 sq. ft. 67m <sup>2</sup>	576 sq. ft. 54m <sup>2</sup>	576 sq. ft. 54m <sup>2</sup>	2800 lbs. 1270kg